



High Production Destruction



EASY OPERATION reduces operator error and fatigue.

COMPACT DESIGN and light weight makes transport simple.

SIMPLE HOOK UP allows for easy change of attachments.

LOW MAINTENANCE and minimal wear items reduces downtime.

HIGH PRODUCTION is maintained due to the broad face of the striking surface which allows for excellent area coverage and production.

LOW INVESTMENT and high production results in the lowest cost per yard ton figures attainable.

SHOCK FREE ground engagement platform system keeps the Hurricane grounded and dissipates the shock as it pulverizes the concrete.





- * Highest Impact to weight ratio in the business
- * No Points to wear out, break, or replace.
- * No Front Head bushings to grease and wear out.
- * No expensive seals to be replaced.
- * No Accumulator to recharge or replace.
- * No Daily or weekly lubrication required.
- * The Hurricane will continue to perform with its same energy until gravity changes.
- * Replaceable bolt on adapter bracket for both skid steer and excavator mounting.
- * Bolt on ground engagement end plate for ease of maintenance.

TECHNICAL DATA	
HD 3700	
Impact Energy Blow	3700 ft/lb class
Blows Per Minute	30
Total Impact Energy (Per Minute)	112,000
Operating Weight	1540 lbs.
Min. Oil Flow Demand	8 GPM
Min. Hyd. Pressure	2200 p.s.i.
Operating Height (with weight extended)	7' 6" (adjustable)
Dimensions (HxWxDx)	5' x 1' 6" x 1' 6"

UNIVERSAL IMPACT TECHNOLOGIES, INC. 86 CONFEDERATE AVENUE JASPER, GEORGIA, 30143 1-800-525-6828 1-706-253-7404 FAX: 1-706-253-0743

Online at www.powersledge.com E-mail: www.universalsales@powersledge.com

AUTHORIZED DEALER: